

Borel

Standard Furnaces & Ovens

Switzerland



TUBE FURNACES 1200 °C TU 1200

Definition: Tubular electric furnace, for all applications.

Construction: Robust construction made of bent plate.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Heating: Working chamber surrounded by heating elements.

Electricity: Single-phase 230 VAC, 50 Hz.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.



Photos for illustration purposes only

MODEL	ITEM CODE	Heated Length (mm)	Tube Dim. (Øxlength) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
TU 1200-20-250	N16148	250	20 x 500	350 x 495 x 380	1.0	22
TU 1200-38-250	N16150	250	38 x 500	350 x 495 x 380	1.3	24
TU 1200-50-250	N16152	250	50 x 500	350 x 495 x 380	1.3	27
TU 1200-20-400	G14527	400	20 x 750	450 x 495 x 380	1.3	22
TU 1200-38-450	N16151	450	38 x 750	500 x 495 x 380	1.8	24
TU 1200-50-450	N16153	450	50 x 750	500 x 495 x 380	1.5	27
TU 1200-105-500	N16155	500	105 x 750	550 x 675 x 430	2.5	54
TU 1200-75-600	G15038	600	75 x 750	650 x 635 x 430	1.9	51
TU 1200-105-700	N16156	700	105 x 1000	800 x 675 x 430	3.7	58
TU 1200-75-800	N16154	800	75 x 1000	850 x 635 x 430	3.5	52
TU 1200-105-900	G15039	900	105 x 1200	950 x 675 x 430	3.5	63

Borel Swiss SA - A Division of SOLO Swiss Group
Place Pury, 3 - CH-2000 Neuchâtel - Switzerland

Tel : +41 (0)32 756 64 00
Fax : +41 (0)32 756 64 48

mail@borel.eu
www.borel.eu